

Item Code: CFS-A01

Chemical Name: Powder dispersion agent

Typical Properties

Appearance: Colorless clear liquid

Density: 0.920~0.930

Active Ingredient Content: min 99%

Applications

Used in low-smoke halogen-free flame-retardant wires and cables, can be coupled with inorganic fillers aluminum hydroxide and magnesium hydroxide, to greatly improve inorganic fillers' compatibility with organic systems and hydrophobic performance of fillers.

Used to couple with inorganic fillers such as kaolin, glass, wollastonite and talc, to improve the compatibility between the inorganic fillers and organic systems (such as polyolefin(PP/PE), EVA) , thermoplastic elastomer, rubber and thermosetting resin, etc).

Used in free radical initiated crosslinking systems and vulcanized crosslinking systems.

Packaging

CFS- A01 is available in 25L PE pails, 200L steel drums or 1000L IBC totes.

Custom packaging possibilities are also available.

Transportation

Not dangerous goods.

More detailed and comprehensive information can be found in the corresponding Safety Data Sheet.

Storage

Stored in a cool, well-ventilated place, and avoid exposure to humidity.

Should be stored in its original containers and used up asap after opening.

The expected shelf life is 12months, when stored in a strictly sealed container and under proper conditions.



Hubei Co-Formula Material Tech Co., Ltd.

Tel.: +86-27-84459282

Web: www.cfmats.com

Email: sales@cfmats.com