

## Technical Data Sheet

---

### CFS-MS01, Silane Terminated Polyether Polymer

CFS-MS01, Silane Terminated Polyether Polymer is also called silyl terminated polyether or silane modified polymer. It is mainly used for sealants and coatings with the structure of a polyether backbone and a functional silane terminal group.

#### Typical Properties:

Chemical Name	Silane Terminated Polyether Polymer
Viscosity (25℃)	32000~42000 mPa·s
Modulus	Low & Medium
Color	Colorless
Appearance	Clear viscous liquid
VOC Content	<1%

#### Applications:

Construction and architecture: Sealants and coatings based on Co-Formula silane terminated polymers are suitable for various types of seals such as building roof, air-conditioning system, cracks repairing, doors and windows, kitchen, toilet and other facilities;

Transport vehicles. Silane-terminated polymer sealants can be directly sprayed and sealed without primer, heating or other curing treatment. Their performance and superiority make them widely used in automobile, high-speed rail and shipbuilding industries.

Assembling. Silane-terminated polymer adhesives and sealants are also used for assembling various products because of their non-bubble formation during curing process, which does not affect the mechanical properties of materials.

#### Packaging:

CFS- MS01 is offered in 25L PE pails, 200L PVF steel drums and 1000L IBC totes.

Please contact Co-Formula team for any special packaging request.

#### Storage:

CFS-MS01 should be stored in a cool, well-ventilated place, and avoid exposure to humidity.

CFS-MS01 should be stored in its original containers and used up asap after opening.

When stored in a sealed and unopened container, CFS- MS01 has a shelf life of 12months.



---

Hubei Co-Formula Material Tech Co., Ltd.

Tel.: +86-27-84459282

Web: [www.cfmats.com](http://www.cfmats.com)

Email: [sales@cfmats.com](mailto:sales@cfmats.com)